

On-grid Inverters

R3 Note Series

4kW / 5kW / 6kW / 8kW / 10kW / 12kW / 15kW

Three Phase, 2 MPPTs



FEATURES



Natural cooling for mute operation



150% DC input oversizing



Remote firmware upgrade



IP65 outdoor design



Wider MPPT voltage range (140 ~ 950V)



Built-in zero export function

R3 Note Series

Model	R3-4K-DT	R3-5K-DT	R3-6K-DT	R3-8K-DT	R3-10K-DT	R3-12K-DT	R3-15K-DT
PV Input Data							
Max. Recommended PV Power [Wp]	6000	7500	9000	12000	15000	18000	22500
Max. PV Power for Single MPPT [Wp]	3000	3750	4500	6000	7500	9000	15000 / 7500
Max. PV Input Voltage [V]	1000						
MPPT Voltage Range [V]	140 ~ 950						
Rated Input Voltage [V]	630						
Start-up Voltage [V]	160						
No. of MPP Trackers	2						
No. of Input Strings per Tracker	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1	2 / 1
Max. PV Input Current [A]	16 / 16	16 / 16	16 / 16	16 / 16	16 / 16	16 / 16	20 / 16
Max. Short-circuit Current per MPPT [A]	20 / 20	20 / 20	20 / 20	20 / 20	20 / 20	20 / 20	26 / 20
DC Switch	Integrated						
AC Output Data							
Rated AC Power [W]	4000	5000	6000	8000	10000	12000	15000
Max. Output Power [VA]	4400	5500	6600	8800	11000	13200	16500
Max. AC Current [A]	6.4	8	9.6	12.8	16	19.2	24
Rated AC Voltage / Range [V]	3 / N / PE, 380, 400; ± 20%						
Grid Frequency / Range [Hz]	50 / 60; ± 5						
Adjustable Power Factor [cosφ]	0.8 leading ~ 0.8 lagging						
Output THDi (@Rated Output)	< 3%						
Efficiency							
Max. Efficiency	98.40%	98.40%	98.40%	98.50%	98.50%	98.50%	98.50%
Euro Efficiency	97.80%	97.80%	97.80%	98.00%	98.00%	98.00%	98.00%
General Data							
Size (Width * Height * Depth) [mm]	455 * 390 * 160			455 * 390 * 175			455 * 390 * 190
Weight [kg]	16.3			18.3			21.6
User Interface	LCD						
Communication	RS485 or Wifi or 4G (optional)						
Ambient Temperature Range [°C]	-25 ~ +60						
Relative Humidity	0 ~ 100%						
Operating Altitude [m]	≤ 4000						
Standby Self Consumption [W]	< 0.2						
Topology	Transformerless						
Cooling	Natural						
Enclosure	IP65						
Noise [dB]	< 30						
Warranty [years]	5 / 7 / 10						
Certifications & Standards							
Grid Regulation	C10/11, PEA, MEA, G98, G99, EN 50549, CEI 0-21, CEI 0-16, IEC 61727, IEC 62116, IEC 60068, IEC 61683						
Safety Regulation	IEC 62109-1, IEC 62109-2						
EMC	EN 61000-3-2, EN 61000-3-3, EN 61000-6-2, EN 61000-6-3, EN 61000-3-11, EN 61000-3-12, IEC 61000-4-16, IEC 61000-4-18, IEC 61000-4-29						
Protection							
	• DC Insulation Monitoring			• AC Overvoltage Protection		• Anti-island Protection	
	• Residual Current Monitoring			• AC Overcurrent Protection		• Over-heat Protection	
	• Input Reverse Polarity Protection			• AC Short-circuit Protection		• DC / AC Surge Protection	